

Product: NUMANCIA ARENA LED 3x57000 NARROW E IP66 04 740 Index: 19.4399.2D81.04



Description

Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information		Category	Outdoor luminaires
		Family	NUMANCIA ARENA LED
		Name	NUMANCIA ARENA LED 3x57000 NARROW E IP66 04 740
		Index	19.4399.2D81.04
		EAN	5902107641597
			$\underbrace{\mathbf{E}}_{ED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{E} \bigoplus \bigoplus_{E} \bigoplus$

Light and electrical data

Light sour	rce	LED
Luminous	s flux LED [lm]	169749
LED powe	er [W]	852,3
Luminaire	e luminous flux [lm]	150408,8
Power of	luminaire [W]	888,8
Luminaire	e's light efficiency [lm/W]	169,2
Color of the	he light [K]	4000
CRI		>70
SDCM (LI	ED sources)	3
Beam ang	gle [°]	(C0-C180) / (C90-C270) - 32,4° / 32
Photobiol	ogical risk class (IEC/EN 62471)	RG0
Protection	n against electric shock	I
Protection	n degree	IP66
Voltage		220240 V, 5060 Hz
Lifetime o	of LED sources [h]	108000
Lx/By		L95/B10
Operating	g temperature range [°C]	-40 ÷ 50
Driver		standard on/off (E)
Circuit loa	ad capacity	1 (B10), 2 (B16), 1 (C10), 2 (C16)

Mechanical data


ш





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Weight [kg]	45
Dimensions [mm]	855 x 764 x 140

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025