

Product: NUMANCIA ARENA LED 1x72000 MEDIUM E IP66 04 740 Index: 19.4399.3481.04



Description

Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information		Category	Outdoor luminaires
		Family	NUMANCIA ARENA LED
		Name	NUMANCIA ARENA LED 1x72000 MEDIUM E IP66 04 740
		Index	19.4399.3481.04
		EAN	5902107641061
			$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \end{array}{\end{array}}$

Light and electrical data

Light source		LED
Luminous flux LED [In	n]	72735
LED power [W]		390
Luminaire luminous fl	ux [lm]	61745,2
Power of luminaire [W	Ŋ	406,7
Luminaire's light effici	ency [lm/W]	151,8
Color of the light [K]		4000
CRI		>70
SDCM (LED sources)		3
Beam angle [°]		(C0-C180) / (C90-C270) - 59° / 57,8
Photobiological risk cl	ass (IEC/EN 62471)	RG0
Protection against ele	ectric shock	I
Protection degree		IP66
Voltage		220240 V, 5060 Hz
Lifetime of LED source	es [h]	108000
Lx/By		L95/B10
Operating temperatur	e range [°C]	-40 ÷ 50
Driver		standard on/off (E)
Circuit load capacity		2 (B10), 4 (B16), 2 (C10), 4 (C16)

Mechanical data


ш





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Weight [kg]	13
Dimensions [mm]	768 x 220 x 140

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025