

Product: NUMANCIA ARENA LED 2x72000 MEDIUM E IP66 04 740 Index: 19.4399.3981.04



Description

Numancia Arena delivers high-efficiency lighting for large-scale outdoor spaces, offering efficiency of up to 196 lm/W. Built for extreme temperatures (-40°C to +40°C) and durable with IP66 and IK09 ratings, it ensures reliable performance in challenging environments. Versatile beam options and high-quality optical systems make it a perfect choice for large sports arenas and other outdoor facilities.

Product information		Category	Outdoor luminaires
		Family	NUMANCIA ARENA LED
		Name	NUMANCIA ARENA LED 2x72000 MEDIUM E IP66 04 740
		Index	19.4399.3981.04
		EAN	5902107641368
			$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{\end{array}}$

Light and electrical data

L	light source	LED
L	uminous flux LED [lm]	145470
L	ED power [W]	780
L	uminaire luminous flux [lm]	123490,5
F	Power of luminaire [W]	813,3
L	uminaire's light efficiency [lm/W]	151,8
C	Color of the light [K]	4000
C	CRI	>70
S	SDCM (LED sources)	3
E	Beam angle [°]	(C0-C180) / (C90-C270) - 59° / 57,8
F	Photobiological risk class (IEC/EN 62471)	RG0
F	Protection against electric shock	I
F	Protection degree	IP66
١	/oltage	220240 V, 5060 Hz
L	ifetime of LED sources [h]	108000
L	_x/By	L95/B10
C	Dperating temperature range [°C]	-40 ÷ 50
C	Driver	standard on/off (E)
C	Circuit load capacity	1 (B10), 2 (B16), 1 (C10), 2 (C16)

Mechanical data


ш





Assembly	mounted on poles
Material	aluminum
Color	RAL 9005 (black)
Diffuser	PMMA lenses and hardened transparent glass
Impact resistant	IK09
Weight [kg]	39
Dimensions [mm]	820 x 455 x 140

A graph of light





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025