

**Product:** NEPTUN INOX LED COMPACT 8000 SH-ORNAMENTAL E IP65 840 / L-1200**Index:** 19.4314.4121.20

## Description

Tightly-closed ceiling luminaires with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Body made of austenitic stainless steel INOX A2 (AISI 304). Optionally available in austenitic stainless steel INOX A4 (AISI 316). Diffuser made of hardened ornamental glass. Perfect to be installed in moist and dusty rooms. The luminaire is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminaire is dedicated for halls, warehouses, underground passes, car parks illumination etc.

## Product information

|          |   |
|----------|---|
| Category | <b>Compact</b>  |
| Family   | <b>NEPTUN INOX LED COMPACT</b>  |
| Name     | <b>NEPTUN INOX LED COMPACT 8000 SH-ORNAMENTAL E IP65 840 / L-1200</b> |
| Index    | <b>19.4314.4121.20</b>  |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | <b>LED</b>                                      |
| Luminous flux LED [lm]                    | <b>9270</b>                                     |
| LED power [W]                             | <b>47,3</b>                                     |
| Luminaire luminous flux [lm]              | <b>8433,9</b>                                   |
| Power of luminaire [W]                    | <b>53,8</b>                                     |
| Luminaire's light efficiency [lm/W]       | <b>156,8</b>                                    |
| Color of the light [K]                    | <b>4000</b>                                     |
| CRI                                       | <b>&gt;80</b>                                   |
| SDCM (LED sources)                        | <b>3</b>  |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 107,6° / 113,2°</b> |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                      |
| Protection against electric shock         | <b>I</b>  |
| Protection degree                         | <b>IP65</b>                                     |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                    |
| Lifetime of LED sources [h]               | <b>60000</b>                                    |
| Lx/By                                     | <b>L80/B10</b>                                  |
| Operating temperature range [°C]          | <b>5 ÷ 35</b>                                   |
| Driver                                    | <b>standard on/off (E)</b>                      |
| Power factor cos φ                        | <b>&gt;0,95</b>                                 |
| Circuit load capacity                     | <b>12 (B10), 19 (B16), 19 (C10), 30 (C16)</b>   |

**Mechanical data**



|                  |   |
|------------------|---|
| Assembly         | directly mounted to ceiling construction or surface mounted on slings |
| Material         | austenitic stainless steel INOX A2 (AISI 304)                         |
| Color            | grey  |
| Diffuser         | SH-ORNAMENTAL (hardened ornamental glass)                             |
| Impact resistant | IK08  |
| Dimensions [mm]  | 1283 x 120 x 72   |

**A graph of light**

