

**Product:** NEPTUN INDUSTRY LED COMPACT 12000 PC-OPAL EDD IP66 840 / 1163X115X110MM

**Index:** 19.4316.1123.21



## Description

Tightly-closed ceiling luminaires with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminaire is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. Luminaire designed for industrial facilities.

## Product information

|          |  |
|----------|--|
| Category | <b>Compact</b>   |
| Family   | <b>NEPTUN INDUSTRY LED COMPACT</b>   |
| Name     | <b>NEPTUN INDUSTRY LED COMPACT 12000 PC-OPAL EDD IP66 840 / 1163X115X110MM</b> |
| Index    | <b>19.4316.1123.21</b>   |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | <b>LED</b>                                    |
| Luminous flux LED [lm]                    | <b>12764</b>                                  |
| LED power [W]                             | <b>67,8</b>                                   |
| Luminaire luminous flux [lm]              | <b>10893</b>                                  |
| Power of luminaire [W]                    | <b>75,3</b>                                   |
| Luminaire's light efficiency [lm/W]       | <b>144,7</b>                                  |
| Color of the light [K]                    | <b>4000</b>                                   |
| CRI                                       | <b>&gt;80</b>                                 |
| SDCM (LED sources)                        | <b>3</b>                                      |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 120,4° / 99°</b>  |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                    |
| Protection against electric shock         | <b>I</b>                                      |
| Protection degree                         | <b>IP66</b>                                   |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                  |
| Lifetime of LED sources [h]               | <b>60000</b>                                  |
| Lx/By                                     | <b>L80/B10</b>                                |
| Operating temperature range [°C]          | <b>-25 ÷ 35</b>                               |
| Driver                                    | <b>DIM DALI (EDD)</b>                         |
| Power factor cos φ                        | <b>&gt;0,95</b>                               |
| Circuit load capacity                     | <b>14 (B10), 23 (B16), 22 (C10), 35 (C16)</b> |

**Mechanical data**



|                  |  |
|------------------|--|
| Assembly         | <b>directly mounted to ceiling construction or surface mounted on slings</b> |
| Material         | <b>polycarbonate</b>   |
| Color            | <b>grey</b>  |
| Diffuser         | <b>PC (opalescent polycarbonate)</b>   |
| Impact resistant | <b>IK10</b>  |
| Dimensions [mm]  | <b>1163 x 115 x 110</b>  |

**A graph of light**

