

Product: LUXCAN PRO 2000 40° EDD 63 840 3F**Index:** 19.4317.1323.63

Description

Product for different applications. Various optics, based on lenses, provide a wide range of possibilities, from the narrow beam, indirect, to the wide beam. Available with the possibility of ordering a non-standard version. Cylindrical spotlight setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for installation on the triphasic track. Body built in extruded aluminium painted with high quality coating.

Product information

| | |
|----------|--|
| Category | Projectors |
| Family | LUXCAN PRO |
| Name | LUXCAN PRO 2000 40° EDD 63 840 3F |
| Index | 19.4317.1323.63 |



Light and electrical data

| | |
|-------------------------------------|---|
| Light source | LED |
| Luminous flux LED [lm] | 2058 |
| LED power [W] | 11,8 |
| Luminaire luminous flux [lm] | 1540,8 |
| Power of luminaire [W] | 13,9 |
| Luminaire's light efficiency [lm/W] | 110,8 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 36,6° / 37° |
| Protection against electric shock | II |
| Protection degree | IP20 |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 83000 (1) / 100000 (2) |
| Lx/By | L90/B10 (1) / L80/B10 (2) |
| Operating temperature range [°C] | 5 ÷ 35 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 47 (B10), 76 (B16), 47 (C10), 76 (C16) |

Mechanical data



| | |
|------------------|---------------------------------------|
| Assembly | mounted on a three-phase track |
| Material | aluminum |
| Color | RAL 9003 (white) |
| Diffuser | transparent PMMA |
| Impact resistant | IK04 |
| Dimensions [mm] | Ø90 x 187 |

A graph of light

