

**Product:** NEPTUN INOX LED 16000 SH-ORNAMENTAL EDD IP65 840 / L-1200

**Index:** 19.4328.6123.20



## Description

Tightly-closed ceiling luminaires with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Body made of austenitic stainless steel INOX A2 (AISI 304). Optionally available in austenitic stainless steel INOX A4 (AISI 316). Diffuser made of hardened ornamental glass. Perfect to be installed in moist and dusty rooms. The luminaire is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. The luminaire is dedicated for halls, warehouses, underground passes, car parks illumination etc.

## Product information


Category	<b>Industrial luminaires</b>
Family	<b>NEPTUN INOX LED</b>
Name	<b>NEPTUN INOX LED 16000 SH-ORNAMENTAL EDD IP65 840 / L-1200</b>
Index	<b>19.4328.6123.20</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>16426</b>
LED power [W]	<b>91</b>
Luminaire luminous flux [lm]	<b>14944,4</b>
Power of luminaire [W]	<b>101,9</b>
Luminaire's light efficiency [lm/W]	<b>146,7</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 107,6° / 113,2°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP65</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>60000</b>
Lx/By	<b>L80/B10</b>
Operating temperature range [°C]	<b>-25 ÷ 35</b>
Driver	<b>DIM DALI (EDD)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>14 (B10), 22 (B16), 14 (C10), 22 (C16)</b>

## Mechanical data



Assembly	<b>directly mounted to ceiling construction or surface mounted on slings</b>
Material	<b>austenitic stainless steel INOX A2 (AISI 304)</b>
Color	<b>grey</b>
Diffuser	<b>SH-ORNAMENTAL (hardened ornamental glass)</b>
Impact resistant	<b>IK08</b>
Dimensions [mm]	<b>1283 x 120 x 72</b>

## A graph of light

