

Product: NEPTUN INDUSTRY LED 19000 PC-OPAL EDD IP66 21 830 / 1563X115X110MM

Index: 19.4329.4213.21



## **Description**

Tightly-closed ceiling luminaries with highly efficient LED light sources, ensuring additional protection against solid body penetration and jet of water from all directions. Perfect to be installed in moist and dusty rooms. The luminary is characterized by compact size and unbelievably simple and quick way to install comparing with similar products. The color temperature for applied LED light sources is 3000/4000 K. Color rendering index Ra>80. Luminaire designed for industrial facilities. Luminaire clips made of steel.

## **Product information**

Category Industrial luminaires		
Family	NEPTUN INDUSTRY LED	
Name	NEPTUN INDUSTRY LED 19000 PC-OPAL EDD IP66 21 830 / 1563X115X110MM	
Index	19.4329.4213.21	











## Light and electrical data

Light source	LED
Luminous flux LED [lm]	18158
LED power [W]	95
Luminaire luminous flux [lm]	15496,4
Power of luminaire [W]	105,6
Luminaire's light efficiency [lm/W]	146,7
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 120,4° / 99°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	-40 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	13 (B10), 21 (B16), 22 (C10), 32 (C16)



Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
	Material	polycarbonate
	Color	RAL 9006 (grey)
	Diffuser	PC (opalescent polycarbonate)
	Impact resistant	IK10
	Dimensions [mm]	1563 x 115 x 110

## A graph of light

