

Product: PAREO ONE LED 2000 AREA E IP66 22 740

Index: 19.4440.1181.22



# **Description**

Modernistic park and garden luminaire. Body made of cast aluminium. Transparent diffuser made of hardened glass. External coating provides high level of resistance to all weather conditions and aesthetic appearance of the luminaire during the whole lifetime (IP66 rating). The diameter of the fitting is 78 mm. The luminaire is especially recommended for squares, parks, open spaces.

### **Product information**

Category	Outdoor luminaires
Family	PAREO ONE LED
Name	PAREO ONE LED 2000 AREA E IP66 22 740
Index	19.4440.1181.22
EAN	5902107311827















# Light and electrical data

Light source	LED
Luminous flux LED [lm]	2440
LED power [W]	10,8
Luminaire luminous flux [lm]	2006
Power of luminaire [W]	12,1
Luminaire's light efficiency [lm/W]	165,8
Color of the light [K]	4000
CRI	>70
Beam angle [°]	(C0-C180) / (C90-C270) - 118,2° / 112,4°
Protection against electric shock	II
Protection against electric shock Protection degree	II IP66
	•
Protection degree	IP66
Protection degree Voltage	IP66 220240 V, 5060 Hz
Protection degree  Voltage  Lifetime of LED sources [h]	IP66 220240 V, 5060 Hz 100000
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	IP66 220240 V, 5060 Hz 100000 L80/B10
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By  Operating temperature range [°C]	IP66 220240 V, 5060 Hz 100000 L80/B10 -40 ÷ 40

# Mechanical data






Assembly	mounted on poles
Material	aluminum
Color	RAL 9007 (dark grey)
Diffuser	hardened transparent glass
Impact resistant	IK09
Weight [kg]	5,55
Dimensions [mm]	Ø490 x 560



# A graph of light



### **Accessories**

Index 19.3266.9999.22

Name PAREO ONE LED REDUCTION 22 76/62mm

