

**Product:** STREETPARK SMALL V2 LED PREMIUM 5600 ROAD E IP66 43 740

**Index:** 19.4402.1981.43



## Description

Streetpark LED Mini/Small combines elegance and efficiency, offering optimal lighting for urban streets, roads, and public spaces. With up to 182 (Mini), 187 (Small) lm/W efficiency, and a lumen output of up to 7523 lm (Mini) and 17287 lm (Small), it ensures excellent visibility while reducing energy consumption. Built to withstand harsh outdoor conditions, it's perfect for a wide range of applications, from main roads to squares. The diameter of the mounting bracket is 60 mm.

## Product information


Category	Outdoor luminaires
Family	STREETPARK SMALL V2 LED PREMIUM
Name	STREETPARK SMALL V2 LED PREMIUM 5600 ROAD E IP66 43 740
Index	19.4402.1981.43
EAN	5902107645762



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5654
LED power [W]	25,8
Luminaire luminous flux [lm]	4964,8
Power of luminaire [W]	28,3
Luminaire's light efficiency [lm/W]	175,4
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Beam angle [°]	street light distribution
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	108000
Lx/By	L95/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	standard on/off (E)
Circuit load capacity	13 (B10), 21 (B16), 21 (C10), 35 (C16)

**Mechanical data**



Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 7035 (light grey)</b>
Diffuser	<b>PMMA lenses and hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>610 x 205 x 85</b>

**A graph of light**

