

**Product:** STREETPARK SMALL V2 LED PREMIUM 13800 ROAD E IP66 43 740

**Index:** 19.4402.1E81.43



## Description

Streetpark LED Mini/Small combines elegance and efficiency, offering optimal lighting for urban streets, roads, and public spaces. With up to 182 (Mini), 187 (Small) lm/W efficiency, and a lumen output of up to 7523 lm (Mini) and 17287 lm (Small), it ensures excellent visibility while reducing energy consumption. Built to withstand harsh outdoor conditions, it's perfect for a wide range of applications, from main roads to squares.

## Product information

Category	<b>Outdoor luminaires</b>
Family	<b>STREETPARK SMALL V2 LED PREMIUM</b>
Name	<b>STREETPARK SMALL V2 LED PREMIUM 13800 ROAD E IP66 43 740</b>
Index	<b>19.4402.1E81.43</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>14436</b>
LED power [W]	<b>72,6</b>
Luminaire luminous flux [lm]	<b>12675,5</b>
Power of luminaire [W]	<b>79,7</b>
Luminaire's light efficiency [lm/W]	<b>159</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;70</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>street light distribution</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>108000</b>
Lx/By	<b>L95/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 50</b>
Driver	<b>standard on/off (E)</b>
Circuit load capacity	<b>19 (B10), 31 (B16), 31 (C10), 51 (C16)</b>

## Mechanical data

Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 7035 (light grey)</b>
Diffuser	<b>PMMA lenses and hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>610 x 205 x 85</b>

## A graph of light

