

**Product:** STREETPARK MINI V2 LED PREMIUM 9200 ROAD E IP66 43 740

**Index:** 19.4403.1D81.43



## Description

Streetpark LED Mini/Small combines elegance and efficiency, offering optimal lighting for urban streets, roads, and public spaces. With up to 182 (Mini), 187 (Small) lm/W efficiency, and a lumen output of up to 7523 lm (Mini) and 17287 lm (Small), it ensures excellent visibility while reducing energy consumption. Built to withstand harsh outdoor conditions, it's perfect for a wide range of applications, from main roads to squares.

## Product information


|          |   |
|----------|---|
| Category | <b>Outdoor luminaires</b>                                     |
| Family   | <b>STREETPARK MINI V2 LED PREMIUM</b>                         |
| Name     | <b>STREETPARK MINI V2 LED PREMIUM 9200 ROAD E IP66 43 740</b> |
| Index    | <b>19.4403.1D81.43</b>  |



## Light and electrical data

|   |   |
|---|---|
| Light source                              | <b>LED</b>                                    |
| Luminous flux LED [lm]                    | <b>9566</b>                                   |
| LED power [W]                             | <b>47,2</b>                                   |
| Luminaire luminous flux [lm]              | <b>7059,3</b>                                 |
| Power of luminaire [W]                    | <b>43,9</b>                                   |
| Luminaire's light efficiency [lm/W]       | <b>160,8</b>                                  |
| Color of the light [K]                    | <b>4000</b>                                   |
| CRI                                       | <b>&gt;70</b>                                 |
| SDCM (LED sources)                        | <b>3</b>                                      |
| Beam angle [°]                            | <b>street light distribution</b>              |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                    |
| Protection against electric shock         | <b>I</b>                                      |
| Protection degree                         | <b>IP66</b>                                   |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                  |
| Lifetime of LED sources [h]               | <b>108000</b>                                 |
| Lx/By                                     | <b>L95/B10</b>                                |
| Operating temperature range [°C]          | <b>-40 ÷ 50</b>                               |
| Driver                                    | <b>standard on/off (E)</b>                    |
| Circuit load capacity                     | <b>15 (B10), 25 (B16), 25 (C10), 40 (C16)</b> |

## Mechanical data



|                  |   |
|------------------|---|
| Assembly         | <b>mounted on poles</b>                           |
| Material         | <b>aluminum</b>                                   |
| Color            | <b>RAL 7035 (light grey)</b>                      |
| Diffuser         | <b>PMMA lenses and hardened transparent glass</b> |
| Impact resistant | <b>IK09</b>                                       |
| Dimensions [mm]  | <b>513 x 180 x 85</b>                             |

## A graph of light

