

**Product:** STREETPARK MINI V2 LED PREMIUM 8000 PARKING E IP66 43 740

**Index:** 19.4403.2C81.43



## Description

Streetpark LED Mini/Small combines elegance and efficiency, offering optimal lighting for urban streets, roads, and public spaces. With up to 182 (Mini), 187 (Small) lm/W efficiency, and a lumen output of up to 7523 lm (Mini) and 17287 lm (Small), it ensures excellent visibility while reducing energy consumption. Built to withstand harsh outdoor conditions, it's perfect for a wide range of applications, from main roads to squares. The diameter of the mounting bracket is 60 mm.

## Product information


Category	<b>Outdoor luminaires</b>
Family	<b>STREETPARK MINI V2 LED PREMIUM</b>
Name	<b>STREETPARK MINI V2 LED PREMIUM 8000 PARKING E IP66 43 740</b>
Index	<b>19.4403.2C81.43</b>
EAN	<b>5902107646721</b>



## Light and electrical data

Light source	<b>LED</b>
Luminous flux LED [lm]	<b>8276</b>
LED power [W]	<b>40</b>
Luminaire luminous flux [lm]	<b>7001,3</b>
Power of luminaire [W]	<b>43,9</b>
Luminaire's light efficiency [lm/W]	<b>159,5</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;70</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>asymmetric light distribution</b>
Photobiological risk class (IEC/EN 62471)	<b>RG0</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP66</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>108000</b>
Lx/By	<b>L95/B10</b>
Operating temperature range [°C]	<b>-40 ÷ 50</b>
Driver	<b>standard on/off (E)</b>
Circuit load capacity	<b>15 (B10), 25 (B16), 25 (C10), 40 (C16)</b>

**Mechanical data**



Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 7035 (light grey)</b>
Diffuser	<b>PMMA lenses and hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>513 x 180 x 85</b>

**A graph of light**

