

**Product:** STREETPARK MINI V2 LED PREMIUM 4200 ASYMMETRIC E IP66 43 740

**Index:** 19.4403.3981.43



## Description

Streetpark LED Mini/Small combines elegance and efficiency, offering optimal lighting for urban streets, roads, and public spaces. With up to 182 (Mini), 187 (Small) lm/W efficiency, and a lumen output of up to 7523 lm (Mini) and 17287 lm (Small), it ensures excellent visibility while reducing energy consumption. Built to withstand harsh outdoor conditions, it's perfect for a wide range of applications, from main roads to squares. The diameter of the mounting bracket is 60 mm.

## Product information

Category	Outdoor luminaires
Family	STREETPARK MINI V2 LED PREMIUM
Name	STREETPARK MINI V2 LED PREMIUM 4200 ASYMMETRIC E IP66 43 740
Index	19.4403.3981.43
EAN	5902107646585



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	4242
LED power [W]	19,4
Luminaire luminous flux [lm]	3626,1
Power of luminaire [W]	21,3
Luminaire's light efficiency [lm/W]	170,2
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP66
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	108000
Lx/By	L95/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	standard on/off (E)
Circuit load capacity	31 (B10), 50 (B16), 50 (C10), 80 (C16)

**Mechanical data**



Assembly	<b>mounted on poles</b>
Material	<b>aluminum</b>
Color	<b>RAL 7035 (light grey)</b>
Diffuser	<b>PMMA lenses and hardened transparent glass</b>
Impact resistant	<b>IK09</b>
Dimensions [mm]	<b>513 x 180 x 85</b>

**A graph of light**

