

**Product:** ARUNA SLIM M LED 8000 OPTICS-1L E 34 840 / L-1200

**Index:** 19.4404.1321.34



## Description

LED luminaire dedicated to be mounted on suspended modular ceilings or using an adaptor frame in plasterboard ceilings (Aruna Slim M LED), directly on the ceiling (Aruna Slim Surface LED) or using slings (Aruna Slim Suspended LED). Equipped with highly efficient LED light sources. Symmetric or asymmetric light distribution. Housing made of steel sheet. Standard colour of the luminaire is white. Colour rendering index CRI: 80.

## Product information

Category	<b>Recessed luminaires</b>
Family	<b>ARUNA SLIM M LED</b>
Name	<b>ARUNA SLIM M LED 8000 OPTICS-1L E 34 840 / L-1200</b>
Index	<b>19.4404.1321.34</b>
EAN	<b>5902107195502</b>



## Light and electrical data



Light source	<b>LED</b>
Luminous flux LED [lm]	<b>8330</b>
LED power [W]	<b>51</b>
Luminaire luminous flux [lm]	<b>6649</b>
Power of luminaire [W]	<b>57</b>
Luminaire's light efficiency [lm/W]	<b>116,6</b>
Color of the light [K]	<b>4000</b>
CRI	<b>&gt;80</b>
SDCM (LED sources)	<b>3</b>
Beam angle [°]	<b>(C0-C180) / (C90-C270) - 100,4° / 90,8°</b>
Protection against electric shock	<b>I</b>
Protection degree	<b>IP20</b>
Voltage	<b>220..240 V, 50..60 Hz</b>
Lifetime of LED sources [h]	<b>100000 (1) / 147000 (2)</b>
Lx/By	<b>L80/B10 (1) / L70/B50 (2)</b>
Operating temperature range [°C]	<b>5 ÷ 30</b>
Driver	<b>standard on/off (E)</b>
Power factor cos φ	<b>&gt;0,95</b>
Circuit load capacity	<b>16 (B10), 26 (B16), 23 (C10), 37 (C16)</b>

**Mechanical data**



Assembly	mounted in module ceilings or using an adaptor frame in plasterboard ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	OPTICS (optical system based on lenses)
Impact resistant	IK04
Dimensions [mm]	1193 x 80 x 40

**A graph of light**



**Accessories**

Index 01ARNL-ASUP  
 Name ARUNA SLIM LED HANDLE FOR SUSPENSION

