

Product: GRANVIA SPOTS 3x 2000 60° E 34 930 / L-1500MM

Index: 19.4406.4531.34



Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Product information

Category	Projectors
Family	GRANVIA SPOTS
Name	GRANVIA SPOTS 3x 2000 60° E 34 930 / L-1500MM
Index	19.4406.4531.34
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	4977
LED power [W]	35,4
Luminaire luminous flux [lm]	3768
Power of luminaire [W]	40,2
Luminaire's light efficiency [lm/W]	93,7
Color of the light [K]	3000
CRI	>90
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	
i roteotion against electric shock	II
Protection degree	IP20
	•
Protection degree	IP20
Protection degree Voltage	IP20 220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	IP20 220240 V, 5060 Hz 100000
Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP20 220240 V, 5060 Hz 100000 L80/B10
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP20 220240 V, 5060 Hz 100000 L80/B10 5 ÷ 35

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	steel sheet and aluminum
Color	RAL 9016 (white)
Diffuser	transparent PMMA
Impact resistant	IK04
Dimensions [mm]	1500 x 72 x 50