

Product: GRANVIA SPOTS 2x 3000 24° EDD 34 940 / L-900MM Index: 19.4406.2443.34



Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Product	information
---------	-------------

Category	Projectors	
Family	GRANVIA SPOTS	
Name	GRANVIA SPOTS 2x 3000 24° EDD 34 940 / L-900MM	
Index	19.4406.2443.34	
EAN	5902107650490	
	$\overbrace{LED} (\overbrace{ED}) (\overbrace{D}) (\overbrace{P_{20}}) (\overbrace{K_{41}}) (\overbrace{D}) (\overbrace{M_{51}})) (\overbrace{M_{51}}) (\overbrace{M_{51}}) (\overbrace{M_{51}}) (\overbrace{M_{51}})) (\overbrace{M_{51}}) (\overbrace{M_{51}}) (\overbrace{M_{51}}) (\overbrace{M_{51}})) (\overbrace{M_{51}}$	

Light and electrical data

Light source	LED
Luminous flux LED [lm]	5155,5
LED power [W]	32,4
Luminaire luminous flux [lm]	3915,1
Power of luminaire [W]	36,8
Luminaire's light efficiency [lm/W]	106,4
Color of the light [K]	4000
CRI	>90
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	20 (B10), 34 (B16), 36 (C10), 57 (C16)

Mechanical data

B



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	steel sheet and aluminum
Color	RAL 9016 (white)
Diffuser	transparent PMMA
Impact resistant	IK04
Dimensions [mm]	900 x 72 x 50

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 09-09-2025