


## Product: GRANVIA SPOTS 3x 2000 24° E 34 MEAT / L-1500MM Index: 19.4406.25D1.34



## Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Product information	


Category	Projectors
Family	GRANVIA SPOTS
Name	GRANVIA SPOTS 3x 2000 24° E 34 MEAT / L-1500MM
Index	19.4406.25D1.34
EAN	5902107651497
	$\overbrace{LED} ( \overbrace{ED} ) ( \overbrace{D} ) ( \overbrace{P_{20}} ) ( \overbrace{K_{41}} ) ( \overbrace{D} ) ( \overbrace{M_{500}} ) ( \overbrace{M_{500} ) ( \overbrace{M_{500}} ) ) ( \overbrace{M_{500}} ) $

## Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	4062
	LED power [W]	32,7
	Luminaire luminous flux [lm]	3084,7
	Power of luminaire [W]	37,2
	Luminaire's light efficiency [lm/W]	82,9
	Color of the light [K]	MEAT
	CRI	>85
	SDCM (LED sources)	3
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	II
	Protection degree	IP20
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	15 (B10), 23 (B16), 23 (C10), 36 (C16)

## Mechanical data





Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	steel sheet and aluminum
Color	RAL 9016 (white)
Diffuser	transparent PMMA
Impact resistant	IK04
Dimensions [mm]	1500 x 72 x 50

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 22-08-2025