

Product: GRANVIA SPOTS 1x 3000 40° EDD 34 BREAD / L-600MM

Index: 19.4406.32E3.34



Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Product information

| Category | Projectors |
|----------|--|
| Family | GRANVIA SPOTS |
| Name | GRANVIA SPOTS 1x 3000 40° EDD 34 BREAD / L-600MM |
| Index | 19.4406.32E3.34 |
| EAN | 5902107650100 |
















Light and electrical data

| Light source | LED |
|--|--|
| Luminous flux LED [lm] | 2399 |
| LED power [W] | 15,8 |
| Luminaire luminous flux [lm] | 1796,6 |
| Power of luminaire [W] | 19 |
| Luminaire's light efficiency [lm/W] | 94,6 |
| Color of the light [K] | BREAD |
| CRI | >85 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | II |
| 1 Totootion against cicotile shook | II . |
| Protection degree | IP20 |
| | • |
| Protection degree | IP20 |
| Protection degree Voltage | IP20 220240 V, 5060 Hz |
| Protection degree Voltage Lifetime of LED sources [h] | IP20 220240 V, 5060 Hz 100000 |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By | IP20 220240 V, 5060 Hz 100000 L80/B10 |
| Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] | IP20 220240 V, 5060 Hz 100000 L80/B10 5 ÷ 35 |

Mechanical data





| Assembly | directly mounted to ceiling construction or surface mounted on slings |
|------------------|--|
| Material | steel sheet and aluminum |
| Color | RAL 9016 (white) |
| Diffuser | transparent PMMA |
| Impact resistant | IK04 |
| Dimensions [mm] | 600 x 72 x 50 |