

Product: GRANVIA SPOTS 2x 3000 40° EDD 34 FRUIT / L-900MM Index: 19.4406.34G3.34



Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Product information	Category	Projectors
	Family	GRANVIA SPOTS
	Name	GRANVIA SPOTS 2x 3000 40° EDD 34 FRUIT / L-900MM
	Index	19.4406.34G3.34
	EAN	5902107651107
		$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$
Light and electrical data	Light source	ce LED
	Luminous f	flux LED [lm] 4389

light and creditioal data		
	Luminous flux LED [I	lm] 4389
	LED power [W]	31,7
	Luminaire luminous	flux [lm] 3286,8
	Power of luminaire [\	W] 36
	Luminaire's light effic	ciency [lm/W] 91,3
	Color of the light [K]	FRUIT
	CRI	>95
	SDCM (LED sources	3
	Photobiological risk (62471)	class (IEC/EN RG0
	Protection against el	ectric shock II
	Protection degree	IP20
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sour	rces [h] 100000
	Lx/By	L80/B10
	Operating temperatu	ıre range [°C] 5 ÷ 35
	Driver	DIM DALI (EDD)
	Power factor $\cos \phi$	>0,95
	Circuit load capacity	20 (B10), 34 (B16), 36 (C10), 57 (C16)
lechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
] =1	Material	steel sheet and aluminum
-	Color	RAL 9016 (white)
	Diffuser	transparent PMMA
	Impact resistant	IK04
	Dimensions [mm]	900 x 72 x 50 Luminous flux tolerance +/- 10%. Power tolerance +/- 1

Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 09-09-2025