

Product: GRANVIA SPOTS 3x 3000 40° E 34 930 / L-1500MM Index: 19.4406.3631.34



Description

GRANVIA SPOTS is a high-performance accent lighting module for the GRANVIA trunking system, designed for precise illumination in supermarkets and commercial spaces. Available in three lengths with up to three Luxcan Pro projectors, it offers flexibility with different beam angles and specialized LED light sources like MEAT, BREAD, FRUIT and PEARL WHITE and high CRI options to ensure vivid, true-to-life colours and enhanced product display.

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 09-09-2025

Category Projectors Family GRANVIA SPOTS	
Family GRANVIA SPOTS	
Name GRANVIA SPOTS 3x 3000 40° E 34 930 / L-1500MM Index 19.4406.3631.34	
Light source	LED
Luminous flux LED [lm]	7512,8
LED power [W]	48,6
Luminaire luminous flux [lm]	5626,2
Power of luminaire [W]	55,2
Luminaire's light efficiency [lm/W]	101,9
Color of the light [K]	3000
CRI	>90
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 19 (B16), 19 (C10), 30 (C16)
	tly mounted to ceiling construction or ce mounted on slings
	sheet and aluminum
	9016 (white)
	parent PMMA
	x 72 x 50
	Light sourceLuminous flux LED [Im]LED power [W]Luminaire luminous flux [Im]Power of luminaire [W]Luminaire's light efficiency [Im/W]Color of the light [K]CRISDCM (LED sources)Photobiological risk class (IEC/EN 62471)Protection against electric shockProtection degreeVoltageLifetime of LED sources [h]Lx/ByOperating temperature range [°C]DriverPower factor cos φCircuit load capacityAssemblyMaterialSteelColorRAL SDiffusertransgImpact resistantIK04