

Product: ARUNA SLIM SURFACE LED 4400 OPTICS-1L E 34 840 / L-1200

Index: 19.4407.1221.34



Description

LED luminary dedicated to be mounted on suspended modular ceilings or using an adaptor frame in plasterboard ceilings (Aruna Slim M LED), directly on the ceiling (Aruna Slim Surface LED) or using slings (Aruna Slim Suspended LED). Equipped with highly efficient LED light sources. Symmetric or asymmetric light distribution. Housing made of steel sheet. Standard colour of the luminary is white. Colour rendering index CRI: 80.

Product information


Category	Surface mounted luminaires
Family	ARUNA SLIM SURFACE LED
Name	ARUNA SLIM SURFACE LED 4400 OPTICS-1L E 34 840 / L-1200
Index	19.4407.1221.34
EAN	5902107195618



Light and electrical data


Light source	LED
Luminous flux LED [lm]	4565
LED power [W]	23,4
Luminaire luminous flux [lm]	3644
Power of luminaire [W]	24,7
Luminaire's light efficiency [lm/W]	147,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 100,4° / 90,8°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	OPTICS (optical system based on lenses)
Impact resistant	IK04
Weight [kg]	2,9
Dimensions [mm]	1193 x 80 x 40

A graph of light



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%.
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 17-02-2026