


Product: KUBIK IN NEW LED K 3X1,7W PC-T E IP65 25 840 / 180X130MM

Index: 19.4409.1321.25



## **Description**

KUBIK IN LED is a high-performance outdoor luminaire designed to highlight building facades with aesthetic accent lighting. It is also ideal for illuminating entrances to underground garages and for lighting walkways and passageways, surrounded by a wall. The new updated version features a simplified, fully aluminum body that improves durability and luminaire tightness, maintaining an IP65 rating for excellent protection against dust and water, and ensuring reliable performance in outdoor conditions. The magnetic mounting system allows for easy, secure installation, reducing setup time. Luminaire offers the same high-quality optics from previous versions, ensuring consistent light output and asymmetric light distribution. The transparent polycarbonate diffuser provides even illumination while protecting against mechanical damage. KUBIK IN LED offers improved design, and enhanced resistance combined with easier and faster installation.

## **Product information**

Category	Outdoor luminaires
Family	KUBIK IN NEW LED
Name	KUBIK IN NEW LED K 3X1,7W PC-T E IP65 25 840 / 180X130MM
Index	19.4409.1321.25
EAN	5902107668945













## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	501	
LED power [W]	5,1	
Luminaire luminous flux [lm]	401	
Power of luminaire [W]	6,4	
Luminaire's light efficiency [lm/W]	62,7	
Color of the light [K]	4000	
CRI	>80	
SDCM (LED sources)	5	
Beam angle [°]	100°+55°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	-25 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,5	
Circuit load capacity	46 (B10), 74 (B16), 74 (C10), 119 (C16)	



Mechanical data							
I							

Assembly	mounted in wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PC-T (transparent polycarbonate)
Impact resistant	IK09
Dimensions [mm]	180 x 130 x 100

## A graph of light



