

Product: X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 04 830 LINE-EP / L-2252MM S-1,5M Index: 19.4412.4511.04



Description

Voltage

Lx/By

Driver

Lifetime of LED sources [h]

Power factor $\cos \phi$

Circuit load capacity

Operating temperature range [°C]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

FIGUELINGINATION	Calegory Surface mounted fulli	manes	
	Family X-LINE SLIM LED LINE	nily X-LINE SLIM LED LINE	
	Name X-LINE SLIM L-DOWN 2252MM S-1,5M	X-LINE SLIM L-DOWN LED 8800 MICRO-PRM E 04 830 LINE-EP / L 2252MM S-1,5M	
	Index 19.4412.4511.04		
Light and electrical data	Light source	LED	
	Luminous flux LED [Im]	8884	
	LED power [W]	43,6	
	Luminaire luminous flux [lm]	6574,2	
	Power of luminaire [W]	49,5	
	Luminaire's light efficiency [lm/W]	132,8	
	Color of the light [K]	3000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
	Photobiological risk class (IEC/EN 62471)	RG0	
	Protection against electric shock	I	
	Protection degree	IP40	

220..240 V, 50..60 Hz

standard on/off (E)

12 (B10), 19 (B16), 20 (C10), 32

100000

L80/B10

5 ÷ 35

>0,95

(C16)

Category Surface mounted luminaires



Mechanical data	∏iH ⊨+ B	Assembly Material Color Diffuser Impact resistant	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04
A graph of light		Dimensions [mm]	2252 x 48 x 70


Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025