

Product: X-LINE SLIM L-DOWN LED 2200 PLX EDD 34 840 LINE-1S / L-564MM S-1,5M Index: 19.4412.8923.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

Category	Surface mounted luminaires			
Family	X-LINE SLIM LED LINE			
Name	X-LINE SLIM L-DOWN LED 2200 PLX EDD 34 840 LINE-1S / L- 564MM S-1,5M			
Index	19.4412.8923.34			
	$\overbrace{LED} \textcircled{\begin{tabular}{ c c c c } \hline \hline$			
Light sou	rce LED			

Light and electrical data

Light source	LED
Luminous flux LED [lm]	2338
LED power [W]	10,9
Luminaire luminous flux [lm]	1496,3
Power of luminaire [W]	12,8
Luminaire's light efficiency [lm/W]	116,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	20 (B10), 31 (B16), 33 (C10), 53 (C16)



Mechanical data	H B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slingsaluminumRAL 9016 (white)PLX (PMMA opal)IK04564 x 48 x 70
A graph of light			$\int_{0}^{105^{\circ}} \int_{0}^{10^{\circ}} \int_{$



Accessories

Index 6E1-500KW341P-5 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



