

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM EDD 24 830 LINE-1S / L-564MM S-1,5M Index: 19.4412.8C13.24



#### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	alion

Category	/ Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LI <mark>NE SLIM</mark> L-DOWN LED 2200 MICRO-PRM EDD 24 830 LINE-1S / L-564MM S-1,5M
Index	19.4412.8C13.24
	$\overbrace{C} \bigoplus \bigoplus \bigoplus  \bigoplus \bigoplus  \bigoplus \bigoplus  \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus$

#### Light and electrical data

Light source		LED
Luminous flux LED	) [lm]	2221
LED power [W]		10,9
Luminaire luminou	s flux [lm]	1643,5
Power of luminaire	e [W]	12,8
Luminaire's light e	fficiency [lm/W]	128,4
Color of the light [H	9	3000
CRI		>80
SDCM (LED sourc	es)	3
Beam angle [°]		(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological ris 62471)	k class (IEC/EN	RG0
Protection against	electric shock	I
Protection degree		IP40
Voltage		220240 V, 5060 Hz
Lifetime of LED so	urces [h]	100000
Lx/By		L80/B10
Operating tempera	ature range [°C]	5 ÷ 35
Driver		DIM DALI (EDD)
Power factor cos q	)	>0,95
Circuit load capaci	ty	20 (B10), 31 (B16), 33 (C10), 53 (C16)



Mechanical data	∏tH ⊨ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 564 x 48 x 70
A graph of light			105° 90° 90° 90° 90° 90° 90° 90° 90

## \_\_\_\_\_

Poland

**LUXIONA** 

### Accessories

# Index 6E1-500KWAN1P-5 Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



#### Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025