

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM EDD 04 840 LINE-1S / L-564MM S-1,5M Index: 19.4412.8C23.04



Description

Lx/By

Driver

Power factor $\cos \phi$

Circuit load capacity

Operating temperature range [°C]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation

Light and electrical data

L-564MM S-1,5M Index 19.4412.8C23.04 Index											
Light source LED Luminous flux LED [Im] 2338 LED power [W] 10,9 Luminaire luminous flux [Im] 1730,1 Power of luminaire [W] 12,8 Luminaire's light efficiency [Im/W] 135,2 Color of the light [K] 4000 CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86° Photobiological risk class (IEC/EN RG0 S2471) Protection against electric shock I Protection degree IP40 Voltage 220.240 V, 5060 Hz					NE-1S /						
Light sourceLEDLuminous flux LED [Im]2338LED power [M]10,9Luminaire luminous flux [Im]1730,1Power of luminaire [W]12,8Luminaire's light efficiency [Im/W]135,2Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Index	19.4412.8	C23.04							
Luminous flux LED [Im] 2338 LED power [W] 10,9 Luminaire luminous flux [Im] 1730,1 Power of luminaire [W] 12,8 Luminaire's light efficiency [Im/W] 135,2 Color of the light [K] 4000 CRI 280 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86° Photobiological risk class (IEC/EN 62471) Protection against electric shock I Protection degree IP40 Voltage 220240 V, 5060 Hz				Œ	LED	E		IP ₄₀	K ₀₄	Indoor	
LED power [W]10,9Luminaire luminous flux [Im]1730,1Power of luminaire [W]12,8Luminaire's light efficiency [Im/W]135,2Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Light sou	rce			L	ED				
Luminaire luminous flux [lm]1730,1Power of luminaire [W]12,8Luminaire's light efficiency [lm/W]135,2Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Luminous	s flux LED [l	m]		2	2338				
Power of luminaire [W]12,8Luminaire's light efficiency [Im/W]135,2Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		LED powe	er [W]			1	L0,9				
Luminaire's light efficiency [lm/W]135,2Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Luminaire	e luminous f	flux [lm]		1	L730,1				
Color of the light [K]4000CRI>80SDCM (LED sources)3Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Power of	luminaire [\	N]		1	L2,8				
CRI >80 SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86° Photobiological risk class (IEC/EN 62471) RG0 Protection against electric shock I Protection degree IP40 Voltage 220240 V, 5060 Hz		Luminaire	e's light effic	ciency [l	m/W]	1	L35,2				
SDCM (LED sources) 3 Beam angle [°] (C0-C180) / (C90-C270) - 88,4° / 86° Photobiological risk class (IEC/EN 62471) RG0 Protection against electric shock I Protection degree IP40 Voltage 220240 V, 5060 Hz		Color of t	he light [K]			4	1000				
Beam angle [°](C0-C180) / (C90-C270) - 88,4° / 86°Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		CRI				>	>80				
Photobiological risk class (IEC/EN 62471)RG0Protection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		SDCM (L	ED sources	5)		3	3				
62471)IProtection against electric shockIProtection degreeIP40Voltage220240 V, 5060 Hz		Beam and	gle [°]			(C0-C18	0) / (C9	0-C270)	- 88,4°	/ 86°
Protection degreeIP40Voltage220240 V, 5060 Hz			ogical risk o	class (IE	EC/EN	F	RG0				
Voltage 220240 V, 5060 Hz		Protection	n against el	ectric sl	nock	I					
, ,		Protection	ו degree			1	P40				
Lifetime of LED sources [h] 100000		Voltage				2	220240	V, 500	60 Hz		
		Lifetime of LED sources [h]		1	L00000						

L80/B10

DIM DALI (EDD)

20 (B10), 31 (B16), 33 (C10), 53

5 ÷ 35

>0,95

(C16)

Category Surface mounted luminaires



Mechanical data	∏H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 564 x 48 x 70
A graph of light			105° 90° 90° 90° 90° 90° 90° 90° 90

Accessories

Poland


LUXIONA

Index 6E1-500KW041P-5 Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025