

Product: X-LINE SLIM L-DOWN LED 2200 PLX E 34 840 LINE-EP / L-572MM S-1,5M Index: 19.4412.1221.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

	Category	/ Surface mounted	l luminaires					
	Family	X-LINE SLIM LED	LINE					
	Name	X-LINE SLIM L-D S-1,5M	OWN LED 22	200 PLX E	34 840	LINE-E	P/L-57	2MM
	Index	19.4412.1221.34						
		CE			IP ₄₀	K ₀₄	Indoor	
ata	Light sou	ırce		LED				
	Luminou	s flux LED [lm]		2338				
	LED pow	ver [W]		10,9				
	Luminair	e luminous flux [lm]		1496,3				
	Power of	f luminaire [W]		12,8				
	Luminair	e's light efficiency [li	m/W]	116,9				
	Color of	the light [K]		4000				
	CRI			>80				
	SDCM (I	ED sources)		2				

Light and electrical data

Light source	LED
Luminous flux LED [lm]	2338
LED power [W]	10,9
Luminaire luminous flux [lm]	1496,3
Power of luminaire [W]	12,8
Luminaire's light efficiency [lm/W]	116,9
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)



Mechanical data	⊟tH ⊨ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 572 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 200 45° 45° 250 30° 45° 45° 45° 45° 45° 45° 45° 45° 45° 45




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

