

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 830 LINE-EL / L-572MM S-1,5M Index: 19.4412.1411.21



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	alion

Product information	Category Surface mounted luminaires		
	Family X-LI	N <mark>E SLIM LE</mark> D LINE	
	Name X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 830 LINE 572MM S-1,5M		2200 MICRO-PRM E 21 830 LINE-EL / L-
	Index 19.44	412.1411.21	
Light and electrical data	Light source		LED
	Luminous flux L	_ED [lm]	2221
	LED power [W]		10,9
	Luminaire lumir	nous flux [lm]	1643,5
	Power of lumina	aire [W]	12,8
	Luminaire's ligh	nt efficiency [lm/W]	128,4
	Color of the ligh	nt [K]	3000
	CRI		>80
	SDCM (LED so	urces)	3
	Beam angle [°]		(C0-C180) / (C90-C270) - 88,4° / 86°

RG0

**IP40** 

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115

L

Photobiological risk class (IEC/EN

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

62471)

Voltage

Lx/By

Driver

Protection degree

Power factor  $\cos \varphi$ 

Circuit load capacity

Curfo on mounted luminaires




Mechanical data	H B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         60°       60°         45°       60°         30°       15°         30°       15°         0°       15°         0°       15°         15°       0°         15°       0°         15°       0°         15°       15°

# Accessories

Poland

**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025