

## Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EL / L-572MM S-1,5M Index: 19.4412.1421.24



### Description

Voltage

Lx/By

Driver

Lifetime of LED sources [h]

Power factor  $\cos \phi$ 

Circuit load capacity

Operating temperature range [°C]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Light and electrical data

			-	
	Family	X-LINE SLIM LED LINE		
	Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 24 840 LINE-EL / L- 572MM S-1,5M		
	Index	19.4412.1421.24		
	Light sou	rce	LED	
	Luminous	s flux <mark>LED [lm]</mark>	2338	
	LED pow	er [W]	10,9	
	Luminair	e luminous flux [lm]	1730,1	
	Power of	luminaire [W]	12,8	
Luminaire's light efficiency [lm/W] Color of the light [K]		e's light efficiency [lm/W]	135,2	
		he light [K]	4000	
	CRI		>80	
	SDCM (L	ED sources)	3	
	Beam an	gle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
	Photobio 62471)	logical risk class (IEC/EN	RG0	
	Protectio	n against electric shock	I	
	Protectio	n degree	IP40	

220..240 V, 50..60 Hz

standard on/off (E)

46 (B10), 74 (B16), 72 (C10), 115

100000

L80/B10

5 ÷ 35

>0,95

(C16)

Category Surface mounted luminaires




Mechanical data	∏tH B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105°       105°         90°       90°         75°       90°         60°       200         45°       60°         45°       300         45°       400         30°       15°         30°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°         0°       15°

# Accessories

Poland


**LUXIONA** 

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025