

Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 830 LINE-EP / L-572MM S-1,5M Index: 19.4412.1511.21



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUCI		auon

Light and electrical data

Category	d luminaires						
Family	nily X-LINE SLIM LED LINE						
Name	X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 21 830 LINE-EP / L- 572MM S-1,5M						
Index	19.4412.1511.21						
	CE	LED (E)		IP ₄₀	K ₀₄	Indoor	
Light sou	rce		LED				
Luminous	s flux LED [lm]		2221				
LED pow	er [W]		10,9				
Luminaire	e luminous flux [lm]		1643,5				
Dowor of	luminaire [W]		12,8				

	,
Power of luminaire [W]	12,8
Luminaire's light efficiency [lm/W]	128,4
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)

>0,95

(C16)

46 (B10), 74 (B16), 72 (C10), 115

Power factor $\cos \phi$

Circuit load capacity




Mechanical data	H B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9006 (grey) Micro-PRM (micro-prismatic diffuser PMMA) IK04 572 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 200 60° 60° 45° 60° 30° 15° 30° 15° 0° 15° 0° 15° 15° 0° 15° 0° 15° 0° 15° 15°

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025