

# Product: X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 04 840 LINE-EP / L-572MM S-1,5M Index: 19.4412.1521.04



### Description

Power factor  $\cos \phi$ 

Circuit load capacity

Category Surface mounted luminaires

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	alion

Light and electrical data

	,						
Family	X-LINE SLIM LED	LINE					
Name	e X-LINE SLIM L-DOWN LED 2200 MICRO-PRM E 04 840 LINE-EP / L- 572MM S-1,5M						
Index	19.4412.1521.04						
	CE	LED E		<b>IP</b> <sub>40</sub>	<b>K</b> <sub>04</sub>	Indoor	
Light sou	urce		LED				
<u>Lum</u> inou	s flux LED [lm]		2338				
LED pow	ver [W]		10,9				
Luminair	e luminous flux [lm]		1730,1				
Power of	f luminaire [W]		12,8				
Luminair	e's light efficiency [li	m/W]	135,2				
Color of	the light [K]		4000				
CRI			>80				
SDCM (L	_ED sources)		3				
Beam ar	ngle [°]		(C0-C180	) / (C90	-C270)	- 88,4°	86°
Photobio 62471)	ological risk class (IE	C/EN	RG0				
Protection against electric shock		lock	I				
Protectio	on degree		IP40				
Voltage			220240	V, 506	0 Hz		
Lifetime	of LED sources [h]		100000				
Lx/By			L80/B10				
Operatin	g temperature rang	e [°C]	5 ÷ 35				
Driver			standard	on/off	(E)		

>0,95

(C16)

46 (B10), 74 (B16), 72 (C10), 115



Mechanical data		Assembly	surface mounted on slings
	ЦЩТ	Material	aluminum
Α	l⊷l B	Color	RAL 9005 (black)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	572 x 48 x 70
A graph of light			105° 90° 75° 60° 60° 45° 45° 45° 45° 45° 45° 45° 45

## Accessories

Poland

**LUXIONA** 


## Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025