

Product: X-LINE SLIM L-DOWN LED 4400 PLX E 24 830 LINE-EL / L-1132MM S-1,5M Index: 19.4412.2111.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Category	Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LINE SLIM L-DOWN LED 4400 PLX E 24 830 LINE-EL / L-1132MM S-1,5M
Index	19.4412.2111.24
	$\overbrace{\text{LED}} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{\end{array}}$

Light and electrical data

L	ight source	LED
L	uminous flux LED [lm]	4442
L	ED power [W]	21,8
L	uminaire luminous flux [lm]	2842,9
P	Power of luminaire [W]	24,8
L	uminaire's light efficiency [lm/W]	114,6
C	Color of the light [K]	3000
C	CRI	>80
S	SDCM (LED sources)	3
В	Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN i2471)	RG0
F	Protection against electric shock	I
P	Protection degree	IP40
V	/oltage	220240 V, 5060 Hz
L	ifetime of LED sources [h]	100000
L	x/By	L80/B10
C	Dperating temperature range [°C]	5 ÷ 35
D	Driver	standard on/off (E)
P	Power factor cos φ	>0,95
C	Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum PLX (PMMA opal) IK04 1132 x 48 x 70
A graph of light			105° 105° 90° 90° 90° 90° 75° 60° 60° 100 60° 100 60° 150 45° 200 45° 250 300 30° 300 15° 0° 15°

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025