

Product: X-LINE SLIM L-DOWN LED 4400 PLX E 04 830 LINE-EP / L-1132MM S-1,5M Index: 19.4412.2211.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

> L IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

Product	inform	ation
Product	IIIIOIIII	auon

Product information		Category	tegory Surface mounted luminaires		
		Family	X-LINE SLIM LED LINE		
		Name	me X-LINE SLIM L-DOWN LED 4400 PLX E 04 830 LINE-EP / L-1132MM S-1,5M		
		Index	ndex 19.4412.2211.04		
Light and electrical data		Light sou	urce	LED	
		Luminou	s flux LED [lm]	4442	
		LED pov	ver [W]	21,8	
		Luminair	e luminous flux [lm]	2842,9	
		Power of	f luminaire [W]	24,8	
		Luminair	e's light efficiency [lm/W]	114,6	
		Color of	the light [K]	3000	
		CRI		>80	
		SDCM (I	_ED sources)	3	
		Beam ar	ngle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°	
		Photobic 62471)	logical risk class (IEC/EN	RG0	

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Protection degree

Power factor $\cos \phi$

Circuit load capacity

Voltage

Lx/By

Driver



Mechanical data	□tH B B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) PLX (PMMA opal) IK04 1132 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 90° 60° 100 45° 200 45° 200 30° 15° 30° 15° 30° 15° 30° 15° 0° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15° 90° 15°

Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025