

Product: X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 24 830 LINE-EP / L-1132MM S-1,5M Index: 19.4412.2511.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Category	Surface mounted luminaires			
Family	X-LINE SLIM LED LINE			
Name	X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 24 830 LINE-EP / L- 1132MM S-1,5M			
Index	19.4412.2511.24			
	$(E) \bigoplus_{\text{LED}} (E) \bigoplus_{\text{LED}} (P_{40}) (IK_{4}) \bigoplus_{\text{Index}} (IK_{4}) (IK$			

Light and electrical data

Light source	LED
Luminous flux LED [Im]	4442
LED power [W]	21,8
Luminaire luminous flux [lm]	3287,1
Power of luminaire [W]	24,8
Luminaire's light efficiency [lm/W]	132,5
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)




Mechanical data	∏tH ⊮ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA) IK04 1132 x 48 x 70
A graph of light			105° 90° 90° 90° 90° 90° 90° 90° 90

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025