

Product: X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 34 830 LINE-EP / L-1132MM S-1,5M Index: 19.4412.2511.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via EL-marked luminaire.

I IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

Product	inform	ation
iiouuot		anon

Light and electrical

n	Category Surface mounted luminaires									
	Family X-LINE SLIM LED LINE									
	Name	Name X-LINE SLIM L-DOWN LED 4400 MICRO-PRM E 34 830 LINE-EP / L- 1132MM S-1,5M								
	Index	19.4412.2	511.34							
			CE	LED	E		IP ₄₀	K ₀₄	Indoor	
data	Light sou	rce			L	ED				
	Luminous	s flux <mark>LED [</mark> l	m]		44	442				
	LED powe	er [W]			2	1,8				
	Luminaire	e luminous t	flux [lm]		32	287,1				
	Power of	luminaire [\	N]		24	4,8				
	Luminaire	e's light effic	ciency [Im	n/W]	1:	32,5				
	Color of t	he light [K]			3	000				
	CRI				>	B0				
	SDCM (L	ED sources	5)		3					
	Beam angle [°]			(0	(C0-C180) / (C90-C270) - 88,4° / 86°					
	Photobiol 62471)	ogical risk o	class (IEC	C/EN	R	G0				

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Protection degree

Power factor $\cos \phi$

Circuit load capacity

Voltage

Lx/By

Driver



Mechanical data		Assembly	surface mounted on slings
	Птн	Material	aluminum
L. A		Color	RAL 9016 (white)
	В	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1132 x 48 x 70
		Dimensions [mm]	1132 X 48 X 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 40° 40° 40° 40° 40° 40° 40° 40




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

