

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 21 830 LINE-EL / L-1692MM S-1,5M Index: 19.4412.3111.21



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
TOULUCE		anon

Product information	Category Su	rface mounted luminaires
	Family X-I	LIN <mark>E SLIM LE</mark> D LINE
		LINE SLIM L-DOWN LED 6600 PLX E 21 830 LINE-EL / L-1692MM 1,5M
	Index 19	.4412.3111.21
		$\overbrace{LED} \textcircled{\begin{tabular}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}{c}$
Light and electrical data	Light source	LED
C .	Luminous flux	x LED [lm] 6663
	LED power [V	M] 32,7
	Luminairo lur	minous flux [lm] /26/ 3

	Luminous flux LED [im]	6663	
	LED power [W]	32,7	
	Luminaire luminous flux [lm]	4264,3	
	Power of luminaire [W]	37,2	
	Luminaire's light efficiency [lm/W]	114,6	
	Color of the light [K]	3000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°	
	Photobiological risk class (IEC/EN 62471)	RG0	
	Protection against electric shock	I	
	Protection degree	IP40	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LED sources [h]	100000	
	Lx/By	L80/B10	
	Operating temperature range [°C]	5 ÷ 35	
	Driver	standard on/off (E)	
	Power factor $\cos \phi$	>0,95	
	Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)	




Mechanical data	∏H B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slingsaluminumRAL 9006 (grey)PLX (PMMA opal)IK041692 x 48 x 70
A graph of light			$\int_{0}^{105^{\circ}} \int_{0}^{10^{\circ}} \int_{$

Accessories

Poland

LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025