

# Product: X-LINE SLIM L-DOWN LED 6600 PLX E 34 840 LINE-EL / L-1692MM S-1,5M Index: 19.4412.3121.34



### Description

Voltage

Lx/By

Driver

Lifetime of LED sources [h]

Power factor  $\cos \phi$ 

Circuit load capacity

Operating temperature range [°C]

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuci		anon

Light and electrical data

	Categor	y Surface mounted luminaire	es		
	Family	amily X-LINE SLIM LED LINE			
	Name	ame X-LINE SLIM L-DOWN LED 6600 PLX E 34 840 LINE-EL / L-1692MM S-1,5M			
	Index	19.4412.3121.34			
	Light so	urce	LED		
	Luminou	us flux <mark>LED [lm]</mark>	7014		
	LED pov	wer [W]	32,7		
	Luminai	re luminous flux [lm]	4489		
	Power o	f luminaire [W]	37,2		
Luminaire's light efficiency [lm/W] Color of the light [K] CRI		re's light efficiency [lm/W]	120,7		
		the light [K]	4000		
			>80		
	SDCM (	LED sources)	3		
	Beam ai	ngle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°		
	Photobio 62471)	ological risk class (IEC/EN	RG0		
	Protectio	on against electric shock	I		
	Protectio	on degree	IP40		

220..240 V, 50..60 Hz

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

100000

L80/B10

5 ÷ 35

>0,95

(C16)



Mechanical data	∏tH ⊨→ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1692 x 48 x 70
A graph of light			$105^{\circ} \qquad 109^{\circ} \qquad 90^{\circ} \qquad$




## Accessories

#### Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

