

#### Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 04 840 LINE-EL / L-1692MM S-1,5M Index: 19.4412.3421.04



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

3

L IP40

RG0

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

(C0-C180) / (C90-C270) - 88,4° / 86°

Product	inform	ation
iiouuot		anon

Product information		Category Surface mounted luminaires		
		Family	X-LINE SLIM LED LINE	
		Name	X-LI <mark>NE SLIM</mark> L-DOWN LED 6600 MICRO-PRM E 04 840 LINE-EL / L- 169 <mark>2MM S</mark> -1,5M	
		Index	19.4412.3421.04	
			$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \end{array}{\end{array}}$	
Light and electrical data		Light sou	burce LED	
		Luminou	us flux LED [lm] 7014	
		LED pov	wer [W] 32,7	
		Luminair	ire luminous flux [Im] 5190,4	
		Power of	of luminaire [W] 37,2	
		Luminair	ire's light efficiency [lm/W] 139,5	
		Color of	f the light [K] 4000	
	C	CRI	>80	

SDCM (LED sources)

Photobiological risk class (IEC/EN

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Beam angle [°]

Protection degree

Power factor  $\cos \phi$ 

Circuit load capacity

62471)

Voltage

Lx/By

Driver



Mechanical data	H B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9005 (black) Micro-PRM (micro-prismatic diffuser PMMA) IK04 2,9 1692 x 48 x 70
A graph of light			$105^{\circ} \qquad 105^{\circ} \qquad 105^{\circ} \qquad 00^{\circ} $

## Accessories

Poland

**LUXIONA** 


# Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025