

### Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 34 840 LINE-EL / L-1692MM S-1,5M Index: 19.4412.3421.34



## Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
iiouuot		anon

Product information	Category Surface mounted luminaires		
	Family X-LINE SLIM LED LIN	E	
	Name X-LINE SLIM L-DOWN 1692MM S-1,5M	LED 6600 MICRO-PRM E 34 840 LINE-EL / L-	
	Index 19.4412.3421.34		
Light and electrical data	Light source	LED	
	Luminous flux LED [lm]	7014	
	LED power [W]	32,7	
	Luminaire luminous flux [Im]	5190,4	
	Deven of London in DAG	07.0	

		32,1	
	Luminaire luminous flux [lm]	5190,4	
	Power of luminaire [W]	37,2	
	Luminaire's light efficiency [lm/W]	139,5	
	Color of the light [K]	4000	
	CRI	>80	
	SDCM (LED sources)	3	
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°	
	Photobiological risk class (IEC/EN 62471)	RG0	
	Protection against electric shock	I	
	Protection degree	IP40	
	Voltage	220240 V, 5060 Hz	
	Lifetime of LED sources [h]	100000	
	Lx/By	L80/B10	
	Operating temperature range [°C]	5 ÷ 35	
	Driver	standard on/off (E)	
	Power factor cos φ	>0,95	
	Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)	



Mechanical data		Assembly	surface mounted on slings
	П	Material	aluminum
Α	l+→l B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1692 x 48 x 70
A graph of light			105° 90° 90° 75° 60° 45° 45° 45° 45° 45° 40° 45° 45° 45° 45° 45° 45° 45° 45




# Accessories

#### Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

