

Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 34 830 LINE-EP / L-1692MM S-1,5M Index: 19.4412.3511.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

FIGUELINIOINATION	Category Surface mounted furnitaires	
	Family X-LINE SLIM LED LINE	
	Name X-LINE SLIM L-DOWN LED 1692MM S-1,5M	
	Index 19.4412.3511.34	
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	6663
	LED power [W]	32,7
	Luminaire luminous flux [lm]	4930,6
	Power of luminaire [W]	37,2
	Luminaire's light efficiency [lm/W]	132,5
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz

100000 L80/B10

5 ÷ 35

>0,95

(C16)

standard on/off (E)

25 (B10), 40 (B16), 39 (C10), 62

Lifetime of LED sources [h]

Power factor $\cos \phi$

Circuit load capacity

Operating temperature range [°C]

Lx/By

Driver

Category Surface mounted luminaires



Mechanical data		Assembly	surface mounted on slings
	П	Material	aluminum
Α	l+→l B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1692 x 48 x 70
A graph of light			105° 90° 75° 60° 45° 45° 45° 45° 45° 40° 40° 45° 45° 45° 45° 45° 45° 45° 45




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

