

ndoe'

 $\mathbb{IP}_{40}$ 

IK<sub>4</sub>

# Product: X-LINE SLIM L-DOWN LED 6600 PLX EDD 34 830 LINE-1EL / L-1692MM S-1,5M Index: 19.4412.3713.34



### Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	informatio	n
FIUUUCI	mormano	

Category	Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LINE SLIM L-DOWN LED 6600 PLX EDD 34 830 LINE-1EL / L- 1692MM S-1,5M
Index	19.4412.3713.34

 $\langle E \rangle$ 

Œ

LED

### Light and electrical data

Light source		LED
Luminous flux LED [Im]		6663
LED power [W]		32,7
Luminaire luminous flux	( [lm]	4264,3
Power of luminaire [W]		37,2
Luminaire's light efficier	ncy [lm/W]	114,6
Color of the light [K]		3000
CRI		>80
SDCM (LED sources)		3
Beam angle [°]		(C0-C180) / (C90-C270) - 96,4° / 90,2°
Photobiological risk clas 62471)	ss (IEC/EN	RG0
Protection against elect	ric shock	I
Protection degree		IP40
Voltage		220240 V, 5060 Hz
Lifetime of LED sources	s [h]	100000
Lx/By		L80/B10
Operating temperature	range [°C]	5 ÷ 35
Driver		DIM DALI (EDD)
Power factor $\cos \phi$		>0,95
Circuit load capacity		17 (B10), 28 (B16), 26 (C10), 41 (C16)



Mechanical data	∏tH ⊨→ B	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 1692 x 48 x 70
A graph of light			$105^{\circ} \qquad 109^{\circ} \qquad 90^{\circ} \qquad$



## Accessories

#### Index 6E1-500KW341P-5 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-9875-3-1,5

#### Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



#### Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT



