

Product: X-LINE SLIM L-DOWN LED 6600 PLX E 34 830 LINE-S / L-1684MM S-1,5M Index: 19.4412.A311.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
Product	IIIIOIIII	auon

Category	y Surface mounted luminaires		
Family	X-LINE SLIM LED LINE		
Name	X-LINE SLIM L-DOWN LED 6600 PLX E 34 830 LINE-S / L-1684MM S-1,5M		
Index	19.4412.A311.34		
	$\overbrace{LED} \bigotimes \bigoplus \textcircled{P_{40}} \widecheck{K_{4}} \bigoplus \overleftrightarrow{M_{600}} $		

Light and electrical data

	Light source	LED
	Luminous flux LED [lm]	6663
	LED power [W]	32,7
	Luminaire luminous flux [lm]	4264,3
	Power of luminaire [W]	37,2
	Luminaire's light efficiency [lm/W]	114,6
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 96,4° / 90,2°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000
	Lx/By	L80/B10
	Operating temperature range [°C]	5 ÷ 35
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data	∏‡H ⊨≓ B	Assembly Material Color Diffuser Impact resistant Weight [kg] Dimensions [mm]	surface mounted on slings aluminum RAL 9016 (white) PLX (PMMA opal) IK04 2,9 1684 x 48 x 70
A graph of light			$\begin{bmatrix} 105^{\circ} & & & & \\ 90^{\circ} & & & & \\ 90^{\circ} & & & & \\ 75^{\circ} & & & & \\ 60^{\circ} & & & & \\ 60^{\circ} & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & & \\ 60^{\circ} & & & & \\ 100 & & & $




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

