

Product: X-LINE SLIM L-DOWN LED 6600 MICRO-PRM E 04 840 LINE-S / L-1684MM S-1,5M Index: 19.4412.A621.04



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation

Light and electrical data

Category	Surface mounted	luminaires					
Family	X-LINE SLIM LED I	LINE					
Name	X-LI <mark>NE SLIM</mark> L-DO 1684MM S-1,5M	WN LED 660	0 MICRO	D-PRM	E 04 840	D LINE-	S/L-
Index	19.4412.A621.04						
	CE			IP ₄₀	K ₀₄	Indoor	
Light sou	rce		LED				
Luminous	s flux LED [lm]	•	7014				
LED pow	er [W]		32,7				
Luminaire	e luminous flux [lm]	ļ	5190,4				

LED power [W]	32,7
Luminaire luminous flux [lm]	5190,4
Power of luminaire [W]	37,2
Luminaire's light efficiency [lm/W]	139,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	25 (B10), 40 (B16), 39 (C10), 62 (C16)



Mechanical data		Assembly	surface mounted on slings
	□‡н	Material	aluminum
Α	l⊷+l B	Color	RAL 9005 (black)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	1684 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 60° 60° 200 45° 60° 45° 300 45° 400 30° 15° 30° 15° 30° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15° 0° 15°


Accessories

Poland

LUXIONA


Index 6E1-500KW041P-3

Name SUSPENSION NEW TYPE-A 04 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025