

Product: X-LINE SLIM L-DOWN LED 13200 MICRO-PRM E 24 830 LINE-S / L-3370MM S-1,5M Index: 19.4412.C611.24



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

Product	inform	ation
FIUUUUL		αιισπ

Category	Surface mounted luminaires
Family	X-LINE SLIM LED LINE
Name	X-LINE SLIM L-DOWN LED 13200 MICRO-PRM E 24 830 LINE-S / L- 3370MM S-1,5M
Index	19.4412.C611.24
	$(\begin{array}{c} \ \ \ \ \ \ \ \ \ \ \ \ \ $

Light and electrical data

Light source	LED
Luminous flux LED [Im]	13326
LED power [W]	65,4
Luminaire luminous flux [lm]	9861,2
Power of luminaire [W]	74,3
Luminaire's light efficiency [lm/W]	132,7
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	11 (B10), 18 (B16), 19 (C10), 31 (C16)




Mechanical data		Assembly	surface mounted on slings
	<u> </u>	Material	aluminum
Α	I ↓ H B	Color	anodised aluminum
A	D	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
			3370 x 48 x 70
		Dimensions [mm]	3370 X 48 X 70
A graph of light			105° 105° 90° 90° 75° 60° 60° 200 45° 60° 45° 300 30° 15° 10° 15° <tr< th=""></tr<>

Accessories

Poland


LUXIONA

Index 6E1-500KWAN1P-3
Name SUSPENSION NEW TYPE-A 24
LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT






Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 30-06-2025