

Product: X-LINE SLIM L-DOWN LED 13200 MICRO-PRM E 34 840 LINE-S / L-3370MM S-1,5M Index: 19.4412.C621.34



Description

Luminaire for building long light lines made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspension. Power supply connection only via ELmarked luminaire.

> L IP40

100000

L80/B10

5 ÷ 35

>0,95

(C16)

220..240 V, 50..60 Hz

standard on/off (E)

11 (B10), 18 (B16), 19 (C10), 31

Product	inform	ation
iiouuot		anon

Product information	Category	/ Surface mounted luminair	25
	Family	X-LINE SLIM LED LINE	
		Name X-LINE SLIM L-DOWN LED 13200 MICRO-PRM E 34 840 3370MM S-1,5M	
	Index	19.4412.C621.34	
Light and electrical data	Light sou	irce	LED
	Luminou	s flux LED [lm]	14028
	LED pow	ver [W]	65,4
	Luminair	e luminous flux [lm]	10380,7
	Power of	luminaire [W]	74,3
	Luminair	e's light efficiency [lm/W]	139,7
	Color of	the light [K]	4000
	CRI		>80
	SDCM (L	ED sources)	3
	Beam an	igle [°]	(C0-C180) / (C90-C270) - 88,4° / 86°
	Photobio 62471)	logical risk class (IEC/EN	RG0

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

Protection degree

Power factor $\cos \varphi$

Circuit load capacity

Voltage

Lx/By

Driver



Mechanical data		Assembly	surface mounted on slings
	ППН	Material	aluminum
Α	l⊷l B	Color	RAL 9016 (white)
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Dimensions [mm]	3370 x 48 x 70
A graph of light			105° 105° 90° 90° 75° 75° 60° 200 45° 60° 45° 45° 30° 15° 30° 15° 90° 90°




Accessories

Index 19.3272.0301.34 Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Index 19.3272.1205.00

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

