

Product: TOPAZ ODG CLEAN ST LED CRI95 P SMOOTH 11000 SHM E IP65 34 940 / 650X650 SUFIT 60MM

Index: 19.4430.4441.34



## **Description**

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. The luminaire can be mounted in a ceiling thickness of 55 mm to 75 mm. The product is adapted to be walked on during maintenance. The luminaire withstands 0.9 kN/m2. Product is equipped in highly efficient LED light source.

## **Product information**

Category	Clean luminaires CRI95
Family	TOPAZ ODG CLEAN ST LED CRI95 SMOOTH
Name	TOPAZ ODG CLEAN ST LED CRI95 P SMOOTH 11000 SHM E IP65 34 940 / 650X650 SUFIT 60MM



19.4430.4441.34

Index













## Light and electrical data

Light source	LED	
Luminous flux LED [lm]	10972	
LED power [W]	66,8	
Luminaire luminous flux [lm]	8679	
Power of luminaire [W]	74,8	
Luminaire's light efficiency [lm/W]	116	
Color of the light [K]	4000	
CRI	>95	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP65	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000	
Lx/By	L80/B10	
Operating temperature range [°C]	5 ÷ 30	
Driver	standard on/off (E)	
Power factor cos φ	>0,95	
Circuit load capacity	7 (B10), 11 (B16), 11 (C10), 18 (C16)	



Mechanical data	Assembly	mounted in suspended ceiling
	Material	steel sheet
	Color	RAL 9016 (white)
l B	Diffuser	SHM (hardened mat glass)
<u></u>	Impact resistant	IK08
	Dimensions [mm]	650 x 650 x 55-75
	Mounting hole [mm]	616 x 616

## A graph of light

