

Product: TOPAZ ODG CLEAN AL LED CRI95 5400 MICRO-PRM SH EDD IP65 33 930 / 600X600

Index: 19.4431.2133.33



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaries (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering "deep red" color, and R13 responsible for rendering "light orange" color). Body of the luminaire made of steel sheet powder coated in white. Special construction of the luminaire allows opening it from the top. Thanks to this, maintenance can be done without littering facilities. Product is equipped in highly efficient LED light source.

Product information

Category	Clean luminaires CRI95
Family	TOPAZ ODG CLEAN AL LED CRI95
Name	TOPAZ ODG CLEAN AL LED CRI95 5400 MICRO-PRM SH EDD IP65 33 930 / 600 \times 600 MICRO-PRM SH EDD IP65
Index	19.4431.2133.33
EAN	5902107868130
















Light and electrical data

Light source	LED		
Luminous flux LED [lm]	5964,5		
LED power [W]	36,3		
Luminaire luminous flux [lm]	4372		
Power of luminaire [W]	40,7		
Luminaire's light efficiency [lm/W]	107,4		
Color of the light [K]	3000		
CRI	>95		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP65		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000		
Lx/By	L80/B10		
Operating temperature range [°C]	5 ÷ 30		
Driver	DIM DALI (EDD)		
Power factor cos φ	>0,95		
Circuit load capacity	14 (B10), 23 (B16), 22 (C10), 35 (C16)		



Mec			
$\mathbb{R}/(\mathbb{R} \times \mathbb{R})$	000	\sim	1
W/I C/ - I			
	пап	u	ala.



Assembly	for specialty or concrete ceilings
Material	steel sheet
Color	RAL 9010 (white)
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Dimensions [mm]	657 x 626 x 50-105
Mounting hole [mm]	603 x 603

A graph of light



