

**Product:** NIX V2 7200 120° E 21 IP65 840 / L-1500 mm (through wire connection)

**Index:** 19.9902.0004.21



## Description

Nix is a range of waterproof LED shades with multiple installation possibilities, to be placed on walls and ceilings or suspended. These luminaires are specifically indicated to light up premises where a high environmental protection is necessary: high levels of humidity, pollution and impact risks, which makes them perfect for industrial spaces such as production halls and warehouses as well as in indoor car parks and technical rooms in commercial spaces.

## Product information


Category	Industrial luminaires
Family	NIX V2
Name	NIX V2 7200 120° E 21 IP65 840 / L-1500 mm (through wire connection)
Index	19.9902.0004.21
EAN	19.9901.0012.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	7623
LED power [W]	47,2
Luminaire luminous flux [lm]	7211,4
Power of luminaire [W]	52,9
Luminaire's light efficiency [lm/W]	136,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	6
Beam angle [°]	(C0-C180) / (C90-C270) - 118° / 106,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	54000
Lx/By	L80/B10
Operating temperature range [°C]	-20 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	33 (B10), 53 (B16), 33 (C10), 53 (C16)

**Mechanical data**



Assembly	<b>directly mounted to ceiling construction or surface mounted on slings</b>
Material	<b>polycarbonate</b>
Color	<b>RAL 9006 (grey)</b>
Diffuser	<b>opalescent polycarbonate</b>
Impact resistant	<b>IK10</b>
Dimensions [mm]	<b>1480 x 72 x 61</b>

**A graph of light**

