

Product: NIX V2 7200 120° E 21 IP65 830 / L-1500 mm (through wire connection)**Index:** 19.9902.0003.34

Description

Nix is a range of waterproof LED shades with multiple installation possibilities, to be placed on walls and ceilings or suspended. These luminaires are specifically indicated to light up premises where a high environmental protection is necessary: high levels of humidity, pollution and impact risks, which makes them perfect for industrial spaces such as production halls and warehouses as well as in indoor car parks and technical rooms in commercial spaces.


Product information

Category **Industrial luminaires**Family **NIX V2**Name **NIX V2 7200 120° E 21 IP65 830 / L-1500 mm (through wire connection)**Index **19.9902.0003.34**

Light and electrical data

Light source	LED
Luminous flux LED [lm]	7166,5
LED power [W]	47,2
Luminaire luminous flux [lm]	6779,5
Power of luminaire [W]	52,9
Luminaire's light efficiency [lm/W]	128,2
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	6
Beam angle [°]	(C0-C180) / (C90-C270) - 118° / 106,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	54000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 35
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	33 (B10), 53 (B16), 33 (C10), 53 (C16)

Mechanical data



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	polycarbonate
Color	RAL 9006 (grey)
Diffuser	opalescent polycarbonate
Impact resistant	IK10
Dimensions [mm]	1480 x 72 x 61

A graph of light

